

Noble Lynda Bossler

Jack-up drilling unit

Owner Noble Drilling, UK
Builder CNIM, France
Delivered 1982

Description

Three-legged cantilever jack-up drilling unit, GustoMSC type CJ46.

Classification

Det Norske Veritas
 ✕1A1 Self-elevating drilling unit

Main dimensions

Length hull	55.4 m
Breadth hull	62.0 m
Depth hull	7.5 m
Design draft	4.0 m

Survival condition

Water depth	64.0 m
Air gap	16.8 m
Wave height	23.0 m
Current	1.2 m/s
Wind speed	42.5 m/s
Spudcan penetration	4.0 m

Main tank capacities

Fuel oil	615 m ³
Drill water	836 m ³
Potable water	175 m ³
Preload	7,280 m ³
Liquid mud	352 m ³
Bulk mud	102 m ³
Bulk cement	102 m ³

Variable and combined load


Variable load up to	2,475 t
Combined drilling load:	
• Survival	220 t
• Operating	570 t

Legs

Leg length	104.3 m
Leg diameter	10.0 m
Spudcan area	105 m ²

Jacking system

Number of pinions	36
Make	BLM
Type	B88



Fixation system

Make	GustoMSC
Type	5000

Cantilever system

Type	classic
Longitudinal reach	12.19 m
Transverse reach	3.66 m

Accommodation

80 persons

Drilling equipment

Drilling depth	7,620 m
Derrick	160 ft - 1,000 kips
Draw works	2,000 hp
Top drive	1,100 hp
Mud pumps	3 x 1,600 hp
BOP 1	13 ⁵ / ₈ " 10,000 psi
BOP 2	21 ¹ / ₄ " 2,000 psi

Machinery/ equipment

Main generator sets	4 x 1,085 kW
Deck cranes	2 x 50 t

GustoMSC services

GustoMSC provided the basic design package, including DNV approval.

Data presented in this product sheet is for information only. Unit specific specifications as provided by the Owner shall prevail.

The Netherlands

Karel Doormanweg 66, 3115 JD, Schiedam
 P.O. Box 687, 3100 AR Schiedam

Telephone +31 (0)10 232 0800
 Telefax +31 (0)10 232 0801

www.GustoMSC.com

GustoMSC